

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

Claims 1-4. (Cancelled).

5. (Previously Presented) A push block device for displacing a workpiece relative to woodworking equipment, comprising:

a main body having a proximal end, a distal end, a longitudinal axis, and a first, generally flat working surface;

a handle component extending from said main body whereby when said first working surface is disposed in parallel facing relation to a top surface of a workpiece, said handle component is disposed predominantly vertically above said main body;

a heel component extending from said main body so as to have a first, operative position, wherein said heel projects vertically below a first plane of said first working surface, and a second, stored position wherein a bottom edge of said heel is disposed in or vertically above said first plane, said heel defining a second working surface disposed in a second plane defined at an angle with respect to said first working surface; and

at least one slip resistant pad secured to at least one of said first and second working surfaces.

6. (Original) A push block device according to claim 5, wherein said at least one pad is over molded to said at least one working surface.

7. (Currently Amended) A push block device ~~according to claim 1~~ for displacing a workpiece relative to woodworking equipment, comprising:

a main body having a proximal end, a distal end, a longitudinal axis, and a first, generally flat working surface for engaging a top surface of a workpiece;

a handle component extending from said main body whereby when said first working surface is disposed in parallel facing relation to the top surface of the workpiece, said handle component is disposed predominantly vertically above said main body; and

a heel component extending from said main body so as to have a first, operative position, wherein said heel projects vertically below a first plane of said first working surface, and a second, stored position wherein a bottom edge of said heel is disposed in or vertically above said first plane, said heel defining a second working surface disposed in a second plane defined at an angle with respect to said first working surface, for selectively engaging a trailing end surface of the workpiece for displacing the workpiece,

wherein said heel includes a head portion defining said second working surface, and first and second legs.

8. (Original) A push block device according to claim 7, wherein said first and second legs are secured to said main body.

9. (Original) A push block device according to claim 8, wherein said first and second legs include pins for being disposed in correspondingly sized and shaped receptacles in said main body.

10. (Original) A push block device according to claim 9, wherein said pins are glued to said receptacles.

11. (Currently Amended) A push block device according to claim 1 for displacing a workpiece relative to woodworking equipment, comprising:

a main body having a proximal end, a distal end, a longitudinal axis, and a first, generally flat working surface for engaging a top surface of a workpiece;

a handle component extending from said main body whereby when said first working surface is disposed in parallel facing relation to the top surface of the workpiece, said handle component is disposed predominantly vertically above said main body; and

a heel component extending from said main body so as to have a first, operative position, wherein said heel projects vertically below a first plane of said first working surface, and a second, stored position wherein a bottom edge of said heel is disposed in or vertically above said first plane, said heel defining a second working surface disposed in a second plane defined at an angle with respect to said first working surface, for selectively engaging a trailing end surface of the workpiece for displacing the workpiece,

further comprising a retention plate for securing said retractable heel to said main body.

12. (Original) A push block device according to claim 11, further comprising at least one slip resistant pad over molded to said plate.

13. (Previously Presented) A method for advancing a workpiece relative to woodworking equipment with a push block comprising:

providing a push block including a main body having a proximal end, a distal end, a longitudinal axis, and a first, generally flat working surface; a handle component extending from said main body whereby when said first working surface is disposed in parallel facing relation to a top surface of a workpiece, said handle component is disposed predominantly vertically above said main body; and a heel component extending from said main body so as to have a first, operative position, wherein said heel projects vertically below a first plane of said first working surface, and a second, stored position wherein a bottom edge of said heel is disposed in or vertically above said first plane, said heel defining a second working surface disposed in a second plane defined at an angle with respect to said first working surface;

engaging a top surface of the workpiece with said first working surface; and  
advancing said workpiece with said push block at least partway past said  
woodworking equipment while said woodworking equipment works upon said  
workpiece.

14. (Original) A method as in claim 13, further comprising displacing said push  
block relative to said workpiece so that the pushblock overhangs a trailing end of the  
workpiece, and engaging said trailing end with said second working surface.

Claim 15. (Cancelled).

16. (Currently Amended) A push block device ~~according to claim 1~~ for  
displacing a workpiece relative to woodworking equipment, comprising:  
a main body having a proximal end, a distal end, a longitudinal axis, and a first,  
generally flat working surface for engaging a top surface of a workpiece;  
a handle component extending from said main body whereby when said first  
working surface is disposed in parallel facing relation to the top surface of the  
workpiece, said handle component is disposed predominantly vertically above said main  
body; and  
a heel component extending from said main body so as to have a first, operative  
position, wherein said heel projects vertically below a first plane of said first working  
surface, and a second, stored position wherein a bottom edge of said heel is disposed  
in or vertically above said first plane, said heel defining a second working surface  
disposed in a second plane defined at an angle with respect to said first working  
surface, for selectively engaging a trailing end surface of the workpiece for displacing  
the workpiece,

' wherein said push block main body and handle are molded from a plastic  
material.

17. (Currently Amended) A push block device ~~according to claim 1~~ for displacing a workpiece relative to woodworking equipment, comprising:  
a main body having a proximal end, a distal end, a longitudinal axis, and a first, generally flat working surface for engaging a top surface of a workpiece;  
a handle component extending from said main body whereby when said first working surface is disposed in parallel facing relation to the top surface of the workpiece, said handle component is disposed predominantly vertically above said main body; and  
a heel component extending from said main body so as to have a first, operative position, wherein said heel projects vertically below a first plane of said first working surface, and a second, stored position wherein a bottom edge of said heel is disposed in or vertically above said first plane, said heel defining a second working surface disposed in a second plane defined at an angle with respect to said first working surface, for selectively engaging a trailing end surface of the workpiece for displacing the workpiece,  
wherein said handle includes a grip portion spaced from said main body and a leg portion extending from said grip portion to said main body.

18. (Currently Amended) A push block device according to ~~claim 1~~ claim 17, wherein said ~~handle comprises a grip portion spaced from said main body and legs extending~~ extend from adjacent each longitudinal end of said grip portion to said main body.